



## 6502 VIBAC® BOPP BOX SEALING TAPE 6502- EASY PRINT

This Easy Printable Industrial Grade packaging tape is specifically designed for automatic carton sealing and other applications that require medium to heavy adhesion.

PROPERTIES			
Total thickness micron	46 micron	Total thickness mils	1.830 mils
Business	Industrial Professional	Industry	Bundling Carton Sealing Splicing
Easy Print	Yes	Backing Type	BOPP
Backing thickness micron	29 micron	Adhesive type	Synthetic Rubber
Color	White	Tensile strength kg/cm	4,64 kg/cm
Elongation at break	165 %	Adhesion to steel g/cm	530,25 g/cm
Rolling ball test (RBT) cm	<2 cm	Shear on cardboard	>41.67 hours
Backing thickness mils	1.160 mils	Tensile strength lb./inch	26.000 lb./inch
Adhesion to steel oz./inch	48 oz./inch	Rolling ball test (RBT) inch	<0.79 inch
Service Temperature F° (Min / Max)	30/140 °F	Service Temperature C° (Min / Max)	(-2)/60 °C
Application Temperature F° (Min / Max)	54/110 °F	Application Temperature C° (Min / Max)	(12)/43 °C
Available width	150.000 mm 144.000 mm	Available length	914.000 m 1500.000 m 1828.000 m
Packaging type	jumbo single roll		

6502